

Solvent Removable Penetrant

ZChek-PT is formulated to exhibit outstanding penetrating characteristics which provide for increased reliability of discontinuity identification. Due to its high flash point, it can be used even in open areas.

Features / Benefits:

- Vivid red Offers high contrast
- High flash point Safe to use in open areas
- High sensitivity Detects fine cracks
- Non halogenated Safe on all metals.

Approvals / Specification compliance:

- ASME
- AMS 2644
- ISO-3452-2
- ASTM E 165

Application:

ZChek-PT is used in the inspection and detection of weld cracks, shrink cracks, casting cracks and porosity.

Typical Properties:

Color	Vivid red
Density	0.84 g/cc
Viscosity @ 40°C	3.8 cSt
Flash point	>93°C

Direction for use:

- · Pre clean the surface.
- · Apply directly on the surface to be checked.
- · Allow enough dwell time for penetration.

Packaging – Available in 520 ml aerosol can and I liter bulk.

ZChem Specialities Pvt.Ltd., No-4, No, 86 F, 3rd main, 2nd cross, Yeshwantpur industrial area, Bangalore-560022,India. Tel.: 080-41758373 Email: info@zchem.in website: www.zchem.in

Disclaimer: We have taken best care to ensure that the information provided in this data sheet is accurate. Our product is guaranteed to conform to the specifications provided. We make no other warranty; hence the liability is limited to replacement of product only.

